



CUSTOMER	CPC
PRODUCT NO.	CS20552
HENTEK NO.	PC003



## PIN ASSIGNMENT

3	—	2	—	3
2	—	3	—	2
7	—	4	—	7
8	—	5	—	8
5	—	7	—	5
6	—	6	—	6
4	—	20	—	4
SHIELD—SHIELD		SHIELD—SHIELD		

## ROLLED UP CABLE



## DESCRIPTION

1. DB 25PIN F+DB 9PIN F—DB 25PIN F+DB 9PIN F; ASSEMBLY;  
NICKEL PLATED; Beige;
2. WIRING: 20C+1;  
OD: 5.0\*5.0MM $\pm$ 0.2MM;
- LENGTH: 1.8M;
3. 100% OPEN, SHORT&MISWIRE TEST;
4. PACKING: POLYBAG Packing
5. ALL MATERIALS MUST BE IN LINE WITH RoHS.

GENERAL TOLERANCES  
(UNLESS SPECIFIED)

LENGTH: X.  $\pm$  1  
.X  $\pm$  0.2  
.XX  $\pm$  0.10  
ANGLE: X° .  $\pm$  1°  
.X°  $\pm$  0° 30'

UNIT:mm		REV:00	NAME	
DRAWING	OYF	2011/01/27	S.P.NO.	HT-2052
CHECK			P.O.NO.	
APPROVE			SIZE	
			PAGE	1/1